



APOLLO MT 150W

With our Apollo series of spotlights we wanted to reduce the design to its bare essential, we took an architects approach with distinct angular design and subtle softer lines. A play with material and surfaces including a casted aluminum body, and with the outside of the reflector visible as a part of the strong expression of APOLLO



Spotlight for ceramic metal halide 150W G12. Die cast aluminium body, powder coat painted. Integral electronic control gear. Rotation 355°. Vertical adjustment +/- 90°. Track mounted with 3-circuit adapter. Voltage 230V. Light source to be ordered separately.

Class of protection IP20, class I White, silvergrey Colours

Weight total 2100g

Light source Metal halide MT 150W/830

Lampholder G12 Luminous flux 15000 lm

Reflector High purity anodised aluminium.

Spot, medium or flood distribution.

Mounting Track mounted with 3-circuit adaptor


Design Jesper Design

Remarks Can not be dimmed. Includes

protective glass.

○ White	Silver
201021	201027
201022	201028
201023	201029
	201021

Lamp MT 150W/830 G12	990013



16°	16° APOLLO MT		
m	Ø	Lux	
1	0,28	71720	
2	0,56	17930	
3	0,84	7969	
4	1,12	4482	
MT	150W	15000lm	

30°	APC	LLO MT
m	Ø	Lux
1	0,54	23146
2	1,09	5786
3	1,63	2572
4	2,14	1447
MT 1	50W	15000lm

49	° APO	LLO MT
m	Ø	Lux
1	0,91	13470
2	1,81	3368
3	2,72	1497
4	3,65	842
MT 150W 15000lm		