



VANITY LED 2000lm

“The Vanity LED is our newest generation of spotlights aimed for the professional market. Designed for a long operating life, with little need for service. Great comfort with integrated passive cooling technology with no distracting noise or moving parts. Made out of high quality casted aluminium, designed with great care with its unique expression and solid quality feeling”.



LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral electronic driver. Integral heatsink.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter. Voltage 230V.

Class of protection	IP20, class I
Colours	White, black
Weight total	1490g
Light source	LED-module
Luminous flux	2000 lm
Power lightsource	24W (3000K)
Connected load	28W (3000K)
Reflector	Alunova metalized, Spot or medium distribution.
Luminaire light output	65 lm/W (VW 3000K)
Colour rendering	Ra 80
Lifetime	50.000h LM70 at Ta 25°C
Mounting	Track mounted with 3-circuit adaptor
Design	Jesper Design
Dimming:	Not dimmable


VANITY LED 2000lm ○ White ● Black

Vw 3000K Spot 18° **203711** **203714**

Vw 3000K Medium 30° **203712** **203715**

Nw 4000K Spot 18° **203721** **203724**

Nw 4000K Medium 30° **203722** **203725**



18° VANITY LED			30° VANITY LED		
m	∅	Lux	m	∅	Lux
1	0,30	11720	1	0,41	5560
2	0,59	2930	2	0,83	1390
3	0,89	1300	3	1,24	618
4	1,18	730	4	1,66	348
3000K 2000lm			3000K 2000lm		